







THIS IS A RoHS
COMPLIANT
COMPONENT/
PRODUCT.



NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 125 VAC
- 2. CURRENT RATING : 1.5 AMP
- 3. CONTACT RESISTANCE : 100 MILLIOHMS MAX.
- 4. INSULATION RESISTANCE: 1000 MEGOHMS MIN.@ 500 VDC
- 5. DIELECTRIC STRENGTH : 750 VAC 60Hz, 1MIN.

MECHANICAL:

- 1. HOUSING MATERIAL : PBT+30%GF. UL94V-0
- 2. PANEL FRAME : CARBON STEEL, POWDER COATING IN BLACK COLOR
- 3. IDC MATERIAL : PC UL94V-0
- 4. CONTACT : PHOSPHOR BRONZE WITH NICKEL PLATING

ENVIRONMENTAL:

- 1. STORAGE : -40°C TO +85°C
- 2. OPERATION : 0°C TO 70°C

CONFORMING TO TIA/EIA 568B
MATES WITH MODULAR PLUG CONFORMING TO TIA-1096-A
PART NUMBER: N4225-168-03

MARK	000000	NEW DESIGN	MORGAN	101216
ECN-NO.		REVISION RECORD	DRAWN	DATE
	UNLESS OTHERWISE SPECIFIED TOLERANCE		SCALE	CHECKED
	Dimension Range	Tolerance	1/1	APPROVED
	X.X	±0.20	UNIT	
	X.XX	±0.15	mm	
X.XXX	±0.10	SIZE	A3	SHEET 1/1
ANGLE	±5°			
Material/Plated/Notes		NAME		
SEE NOTE		24口C6 非屏蔽配線架		
Tooling No.	PART NO. N4225-168-03		REV. 0	
	DOC. NO. NN422A168			